VAISALA

CAB100 CMS Industrial Cabinet
Large Cabinet for Intrinsically Safe (Exi) Devices

Please choose one attribute from each numbered category and add the corresponding mark to the grid on top of the table.

As a result configuration code for the Vaisala device is formed. Example of order code with typical settings:

| CAB100 | B | 1 | N | G | N | 0 | 0 | N | A | 0 | N | 1 | N |

Selections in bold are included in the prices of the basic versions.

Selections in italic are available at an extra price.

			1	2	3	4	5	6	7	8	9	10	11	12	13
Vaisala Industrial Cabinet Configuration			B	1	N		N	0	0	N	A		N		N
1. Cabinet size															
Large	600 x 500 x 200 (mm) / 23,6 x 19,7 x 7,9 (in)		**B**												
2. Powering															
Power supply	110-240 VAC / 24 VDC			**1**											
				N											
4. Intrinsically safe transmitter connection															
None						**0**									
Safety Barrier quantity 1						1									
Safety Barrier quantity 2						2									
Safety Barrier quantity 3						3									
Safety Barrier quantity 4						4									
Safety Barrier quantity 5						5									
Safety Barrier quantity 6						6									
Safety Barrier quantity 7						7									
Safety Barrier quantity 8						8									
Safety Barrier quantity 9						9									
Safety Barrier quantity 10						A									
Safety Barrier quantity 11						B									
Safety Barrier quantity 12						C									
Safety Barrier quantity 13						D									
Safety Barrier quantity 14						E									
Safety Barrier quantity 15						F									
Safety Barrier quantity 16						G									
Galvanic Isolator quantity 1						H									
Galvanic Isolator quantity 2						J									
Galvanic Isolator quantity 3						K									
Galvanic Isolator quantity 4						L									
Galvanic Isolator quantity 5						M									
Galvanic Isolator quantity 6						N									
Galvanic Isolator quantity 7						P									
Galvanic Isolator quantity 8						R									
Galvanic Isolator quantity 9						S									
Galvanic Isolator quantity 10						T									
Galvanic Isolator quantity 11						U									
Galvanic Isolator quantity 12						V									
							N								
								0							
									0						
										N					
9. Communication															
Port Server (DIGI TS4)	1 port Ethernet RJ-45 10/100 Mbps										**A**				
10. Ethernet Switch															
None												**0**			
1 pcs Ethernet Switch	To optionally add number of Ethernet ports from 1 to 5 pcs, RJ-45 10/100 Mbps (not used in standard installation)												1		
													N		
12. Housing Bottom Flange Material (Housing Top Flanges Rubber as standard)															
Rubber flanges	2 x 25 ports (Multigate MC25) with cable clamp bars													**1**	
Stainless Steel Flanges	2 x 11 pcs EMC protected cable clands and 2 x 5 pcs optional ports													2	
														N	